

SPC VINYL FLOORING

183 x 1220

0,30WL / 32.CLASS

4.0-5.0-6-6.5-7-8 mm



100%
WATERPROOF



DURABLE &
LONG LASTING



PET FRIENDLY &
SCRATCH RESISTANT



ECO FRIENDLY &
SAFE

HF002-01

SPIER-IN

Windows and more

HF002-02

SPIER-IN

Windows and more

HF003-01

SPIER-IN

Windows and more

HF011-03

SPIER-IN
Windows and more

HF012-02

SPIER-IN

Windows and more

HF013-01



HF019-01



HF019-02

SPIER-IN

Windows and more

HF019-03



HF045-01

SPIER-IN

Windows and more

HF015-01



HF015-02



HF015-04



HF016-01



HF016-03



SPC VINYL FLOORING

Our SPC vinyl flooring combines advanced technology with elegant design to deliver superior performance.

Engineered for water resistance, stability and durability, it is the perfect solution for modern living spaces.

UV PROTECTIVE COATING
Protects against stains, scratches and UV rays.

WEAR LAYER
High resistance to daily wear and tear.

DECORATIVE FILM LAYER
Realistic wood or stone look with high definition.

SPC CORE
Rigid core for dimensional stability and impact resistance.

IXPE UNDERLAY
Provides sound absorption and walking comfort.



FEATURES & BENEFITS



100%
WATERPROOF



SOUND
REDUCTION



EASY
CLEAN



PET FRIENDLY &
SCRATCH RESISTANT



FAST & SECURE
CLICK SYSTEM



BEVELED
EDGE



FIRE
RESISTANT



RESIDENTIAL
15 YEAR
WARRANTY

TECHNICAL TEST RESULTS

TEST ITEM	STANDARD	RESULT
Formaldehyde Emission	EN717	E1
Smoke Generation	EN ISO 9239-1	Class S1
Critical Heat Flux	EN ISO 9239-1	Class B
Flame Spread	EN ISO 11925-2	Class B
Reaction to Fire	EN 13501-1	Bfl-s1
Dimensional Stability	EN ISO 10582:2017	<= 0.10%
Curling After Exposure to Heat	EN ISO 23999:2025	<= 0.20%
Resistance to Chemicals	EN ISO 26987:2008	Passed
Stain Resistance	EN ISO 24336	>= 2000 kg/m2
Wear Resistance	EN ISO 10582	<= 0.15%
Indentation Resistance	EN ISO 24343-1	<= 0.02 mm
Thermal Conductivity	EN ISO 10456	0.0437 m2.K/W
Slip Resistance	DIN EN 16165	R10
Castor Chair Test	EN ISO 4918	No Damage

SPECIFICATIONS

PRODUCT TYPE	SPC VINYL FLOORING
SIZE	180 x 1220 mm / 220 x 1220 mm / 305 x 610 mm
THICKNESS	4.0 mm / 5.0 mm / 6.0 mm / 6.5 mm / 7.0 mm / 8.0 mm
WEAR LAYER	0.3 mm / 0.5 mm / 0.55 mm
SURFACE TREATMENT	UV COATING
SURFACE TEXTURE	WOOD EMBOSSED / STONE / EIR
INSTALLATION	UNILIN CLICK SYSTEM
UNDERLAY	IXPE 1.0 mm

IDEAL FOR EVERY SPACE



LIVING ROOM



KITCHEN



BATHROOM



BEDROOM



COMMERCIAL SPACES



100%
WATERPROOF



DURABLE &
LONG LASTING



PET FRIENDLY &
SCRATCH RESISTANT



EASY
MAINTENANCE



ECO FRIENDLY
& SAFE



FAST & EASY
INSTALLATION